

SAFETY DATA SHEET

In according with 3rd revision GHS

Revision Date: 22 May 2017

Section 1 - Identification

Product Name : U511H

Product Type : POLIMAXX® UHMWPE

Product Use : High Impact Ram Extrusion, Sheet, Rod, Profile

Manufacturer : IRPC Public Company Limited

299 Moo 5 Sukhumvit Road Amphur Muang Rayong THAILAND

Emergency Call : +66(0) 38 802560

Website : www.irpc.co.th, www.irpcmarket.com

Section 2- Hazards Identification

Classification according to Regulation (EC) No 1272/2008 (CLP) and GHS Classification:

This product is not classified as dangerous according to Regulation (EC) No 1272/2008 and GHS

Pictogram : Not applicable
Signal Word : Not classified

Hazard Statement : Precautionary Statement : -

Section 3 - Composition / Information on Ingredients

| Chemical Name | CAS Number | EC Number | Percent weight |
|---------------|------------|-----------|----------------|
| Polyethylene | 9002-88-4 | Polymer | >98 |
| 1-Butene | 106-98-9 | 203-449-2 | <2 |





Section 4 - First-aid Measures

Skin Exposure : If molten material comes in contact with the skin, cool under ice water or a running

stream of water. DO NOT attempt to remove the material from the skin. Remove

could result in serve tissue damage. Get medical attention.

Eyes Exposure : If molten material should splash into eyes, flush eyes immediately with fresh water

for 15 minutes while holding the eyelid open. Remove contact lenses, if worn. Get

immediate medical attention.

Inhalation : Move the exposed person to fresh air. If breathing is difficult, give oxygen. Get

medical attention if breathing difficulties continue.

Ingestion : Not a probable route of exposure. If person is conscious, rinse mouth with water.

Do not induce vomiting unless directed to do so by a physician.

Section 5 - Fire-fighting Measures

Suitable extinguishing agents : Dry chemical, foam, water fog or carbon dioxide. Avoid using direct

streams of water on molten burning material

Hazards during fire-fighting : Carbon monoxide, carbon dioxide, original monomer other hydrocarbon

oxidation products include

Protective equipment : Use a mask with universal filler. Use self-contained breathing apparatus

and full protective clothing.

Section 6 - Accidental Release Measures

Personal precautions : Avoid inhalation and direct contact.

Environmental precautions : Discharge into the environment must be avoided.

Cleanup : Collect spilled material using a method that minimizes dust generation

(e.g. wet methods, HEPA vacuum). Place waste in an appropriate

container for disposal. Use care during clean-up to avoid exposure to the

material and injury from broken containers.

Section 7 - Handling and Storage

Handling : Use with adequate ventilation. Avoid dust generation. Avoid contact with eyes and

skin. Accumulations of dust should be removed from settling areas.

Storage conditions: Store in a cool, dry, well-ventilated area or silo away from sources of heat, flame and

sparks. Ventilate enclosed storage areas, such as trailers and railcars, before entering. Have emergency equipment for fires and spills readily available.





Section 8 - Exposure Controls / Personal Protection

Exposure limits

| Component Name | Reference | TWA | | OEL | |
|----------------|---------------------|-----|-------|-----|-------|
| | | ppm | mg/m3 | ppm | mg/m3 |
| Polyethylene | Italy OEL | - | 10 | - | - |
| | Japan OEL for Dusts | - | - | - | 8 |

Personal protective equipment

 $Respiratory\ protection\ :\ Wear\ respiratory\ protection\ if\ ventilation\ is\ inadequate.\ Breathing\ protection$

device if dust is formed.

Eye protection : Wear safety glasses with side shields, goggles or face shield.

Protective clothing : Gloves required when handling hot material. In case of fire, wear MSHA/NIOSH

approved self-contained breathing apparatus or equivalent and full protective

gear.

Ventilation : Provide adequate ventilation when processing material at elevated temperatures.

Other protective equipment: N.A

Engineering Controls: For molten materials: Provide mechanical ventilation; in general such ventilation

should be provided at compounding/ converting areas and at fabricating/ filling work stations where the material is heated. Local exhaust ventilation should be used over and in the vicinity of machinery involved in handling the molten

material.

Section 9-Physical and Chemical Properties

Physical Description : White powder **Odor** Slight to none pН Not applicable **Vapor Pressure** Not applicable **Vapor Density** Not applicable **Boiling Point** Not applicable 130-135°C **Melting Point** Flash Point Not applicable **Auto-ignition** Not applicable **Solubility** Insoluble in water 0.925 - 0.940 @ 25 °C **Specific Gravity** $0.925 - 0.940 \text{ g/cm}^3$ **Density Bulk Density** $350-500 \text{ kg/m}^3$ **Evaporation Rate** Not applicable Volatile matter (wt) Not applicable Water absorption (wt) Not applicable





Section 10 - Stability and Reactivity

Stability : This material is considered a stable thermoplastic, with no chemical

reactivity under normal ambient and anticipated handling conditions of

temperature and pressure.

Condition to Avoid : Avoid heating above the recommended processing temperature. DO NOT heat

without adequate ventilation.

Material to Avoid : May react with strong oxidizing agents, such as chlorates, nitrates, peroxides,

etc. May react with free halogens.

Dangerous decomposition: Small quantities of low molecular weight hydrocarbons, alcohols, aldehydes

(incl. Formaldehyde), carboxylic acids, carbon oxides and ketones can be

formed during thermal processing.

Hazardous polymerization products: Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Acute Toxicity

| Chemical name | Route | Species | Acute Toxic Value | |
|---------------|------------|---------|--|--|
| Polyethylene | Oral | Rat | LD ₅₀ > 3000 mg/kg | |
| rolyethylene | Inhalation | Mouse | LC ₅₀ 12000 mg/m ³ /3M | |

Irritating/corrosive effects

Eye Irritation : Solid particles may cause transient irritation from mechanical abrasion

Skin Irritation : Not expected to cause skin irritation. Molten material may cause thermal burns.

Inhalation : Not a likely route of exposure. Process fumes may cause irritation

Ingestion : May cause a choking hazard if swallowed.

Section 12 - Ecological Information

Eco-toxicity : No relevant studies identified.

Persistence and degradability : This material is not expected to be readily biodegradable.

Bio-accumulative potential: Product is not likely to accumulate in biological organisms.

Mobility in soil : This product has not been found to migrate through soils.

Other adverse effects : The product does not have any known adverse effects on the

environment.





Section 13 - Disposal Considerations

Disposal Methods:

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material)

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - Transport Information

| Regulatory information | UN number | Class | Packing group | Label | Additional information |
|------------------------|---------------|-------|------------------|-------|------------------------|
| DOT | Not regulated | - | ı | - | - |
| ADR / RID | Not regulated | - | - | - | - |
| IMDG CODE | Not regulated | - | - | - | - |
| ICAO / IATA | Not regulated | - | - | - | - |

Section 15 - Regulatory Information

US Toxic Substances Control Act

All components of this product are on the TSCA Inventory.

European Inventory of Existing Commercial Chemical Substances (EINECS)

The components of this product are on the EINECS inventory or are exempt from inventory requirements.

EU Directives 67/548/EEC, 1999/45/EC and Regulation (EC) No 1272/2008

The product is not classified as dangerous for supply according to the Regulation (EC) No 1272/2008 and the EC directive 67/548/EEC and 1999/45/EC.

NFPA - USA

Health – 1, Flammability – 1, Reactivity – 0

Canada - WHMIS

This product does not meet WHMIS classification criteria.

Canada - DSL

This product is listed in DSL.





Section 16 - Other Information

The information in this document is based on our best present. Nevertheless, it does not constitute a guarantee for any specific product features and does not establish any a legally binding contract.

DOT : Department of Transportation

ADR : European agreement concerning the international carriage of dangerous goods

by road.

RID : Regulations concerning the international carriage of dangerous goods by rail.

IMDG – CODE : International maritime dangerous goods code

ICAO : International Civil Aviation Organization
IATA : International air transport association

GHS : Globally Harmonized System of Classification and Labeling of Chemicals

NFPA : National Fire Protection Association

WHMIS : Workplace Hazardous Materials Information System

DSL : Domestic Substances List

The information above is believed to be accurate and represents the best of our knowledge, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.

