

SAFETY DATA SHEET

Revision Date : 18 March 2021

Section 1 – Identification

Product Name : GA300
Product Type : General Purpose ABS
Product Use : Can be used to produce injection or extrusion molded articles for commercial or Industrial products.
Manufacturer : IRPC Public Company Limited
 299 Moo. 5 Sukhumvit Road, Amphur Muang, Rayong THAILAND
Emergency Call : +66(0)38 802560
Website : www.irpc.co.th, <https://polimaxx.irpc.co.th>

Section 2 – Hazards Identification

Classification according to Regulation (EC) No. 1272/2008 (CLP) and GHS Classification :

This product is not classified as dangerous according to Regulation (EC) No 1272/2008 and GHS

Pictogram : Not Applicable

Signal Word : Not applicable

Hazard Statement :

-

Precautionary Statement :

-

Section 3 – Composition / Information on Ingredients

| Chemical Name | CAS Number | EC Number | Percent weight |
|---|------------|-----------|----------------|
| Acrylonitrile Butadiene Styrene Copolymer | 9003-56-9 | Polymer | 97-99 |
| Styrene | 100-42-5 | 202-851-5 | < 0.5 |

Section 4 – First-aid Measures

- Skin Exposure** : In case of skin contact with hot polymer immediately immerse in or flush with clean, cold water.If irritation develops, seek medical attention.
- Eyes Exposure** : If molten material should splash into eyes, flush eyes immediately with fresh water for 15 minutes while holding the eyelid open.Remove contact lenses, if worn.Get immediate medical attention.
- Inhalation** : Move the exposed person to fresh air.If breathing is difficult, give oxygen.Get medical attention if breathing difficulties continue.
- Ingestion** : If person is conscious, rinse mouth with water.Seek medical attention if a significant amount is swallowed.

Section 5 – Fire-fighting Measures

- Suitable extinguishing agents** : Dry chemicals, foam, water, carbon dioxide and halon.
Avoid using direct streams of water on molten burning material.
- Hazards during fire-fighting** : Carbon monoxide, carbon dioxide, original monomer other hydrocarbon oxidation products.
- Protective equipment** : Wear self-contained respiratory protective device.

Section 6 – Accidental Release Measures

- Personal precautions** : Avoid breathing vapors, mist or gas.
- Environmental precautions** : Discharge into the environment must be avoided.

Cleanup :

Collect spilled material using a method that minimizes dust generation (e.g., wet methods, HEPA vacuum).Use care during clean-up to avoid exposure to the material and injury from broken containers.

Section 7 – Handling and Storage

- Handling** : Exposure of polystyrene to extremely high temperatures (315 C or higher) may cause partial decomposition.Chemicals that may be released include styrene monomer, benzene, and other hydrocarbons.Filter and ventilate dust where necessary.
- Storage conditions** : Store in cool location and ventilated place.Store below 50 °C.Keep away from moisture, excessive heat and sources of ignition.Do not place in direct sunlight.

Section 8 – Exposure Controls / Personal Protection

Exposure limits :

| Component Name | Reference | TWA | | STEL | | | |
|----------------|-----------|-----|-------|------|-------|---|---|
| | | ppm | mg/m3 | ppm | mg/m3 | | |
| Styrene | ACGIH TLV | 20 | - | 40 | - | - | - |
| | OSHA PEL | 100 | - | - | - | - | - |

Personal protective equipment

- Respiratory protection : Wear respiratory protection if ventilation is inadequate. Breathing protection device if dust is formed.
- Eye protection : Chemical workers goggles recommended.
- Protective clothing : Gloves required when handling hot material. In case of fire, wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear.
- Ventilation : Provide adequate ventilation when processing material at elevated temperatures.
- Other protective equipment : Ensure that eyewash stations and safety showers are proximal to the work-station location.
- Engineering Controls : For molten materials: Provide mechanical ventilation; in general such ventilation should be provided at compounding/ converting areas and at fabricating/filling work stations where the material is heated. Local exhaust ventilation should be used over and in the vicinity of machinery involved in handling the molten material.

Section 9 – Physical and Chemical Properties

| | |
|--|---------------------------------|
| Appearance | : Pellet |
| Odour | : Characteristic odor |
| Colour | : |
| Boiling Point | : Not Applicable |
| Initial Boiling Point | : |
| Flash Point | : Not Applicable Not Applicable |
| Melting Point | : Not Applicable |
| Vapour Pressure | : Not Applicable |
| Auto ignition temperature | : Not Applicable |
| Solubility | : Soluble in polar solvent |
| Viscosity | : Not Applicable Not Applicable |
| Upper/Lower flammability or explosive limit | : Not Applicable |
| pH | : Not Applicable |
| Relative density | : Not Applicable Not Applicable |
| Vapour density | : |
| Partition characteristics | : |
| Specific Gravity | : 1.04-1.05 |
| Partition coefficient: n-octanol/water | : Not Applicable |
| Decomposition temperature | : Not Applicable |
| Explosive properties | : Not Applicable |
| Softening Point | : > 100 Degree Celcius |

Section 10 – Stability and Reactivity

| | |
|--------------------------------|---|
| Stability | : Stable under normal ambient temperature. |
| Condition to Avoid | : Avoid temperatures above 300°C. |
| Material to Avoid | : Avoid solvents and oxidizing agents. |
| Dangerous decomposition | : Carbon dioxide, carbon monoxide, hydrocarbons, dense smoke. |

Section 11 – Toxicological Information

Acute Toxicity :

| Chemical name | Route | Species | Acute Toxic Value |
|---------------|-------|---------|-------------------|
| Styrene | Oral | Rat | LD50 5,000 mg/kg |

Irritating/corrosive effects

Eye Irritation : Prolonged contact can causes eye irritation.

Skin Irritation : May cause skin irritation.

Inhalation : May cause allergic respiratory response.

Ingestion : Swallowing larger amounts may cause injury.

Section 12 – Ecological Information

Eco-toxicity : No relevant studies found.

Persistence and degradability : The product is not easily biodegradable.

Bio-accumulative potential : Not expected to be bio-accumulative.

Mobility in soil : No data available.

Other adverse effects :

Section 13 – Disposal Considerations

Disposal methods:

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. Dispose of by: burial in a land-fill specifically licensed to accept chemical and/or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material) Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 – Transport Information

| Regulatory information | UN number | Classes | Packing group | Label | Additional information |
|------------------------|---------------|---------|---------------|-------|------------------------|
| DOT | Not regulated | - | - | - | |
| ADR/RID | Not regulated | - | - | - | |
| IMDG CODE | Not regulated | - | - | - | |
| ICAO/IATA | Not regulated | - | - | - | |

Section 15 – Regulatory Information

US Toxic Substances Control Act

All components of this product are on the TSCA Inventory.

European Inventory of Existing Commercial Chemical Substances (EINECS)

The components of this product are on the EINECS inventory or are exempt from inventory requirements.

Canada – WHMIS

Material is not controlled under WHMIS.

Section 16 – Other Information

| | |
|-----------|--|
| ACGIH | : American Conference of Industrial Hygienists |
| ADR | : European agreement concerning the international carriage of dangerous goods by road. |
| CLP | : Classification and Labeling of Packaging |
| DOT | : Department of Transportation |
| GHS | : Globally Harmonized System of Classification and Labeling of Chemicals |
| HMIS | : Hazardous Materials Identification System |
| IATA | : International air transport association |
| ICAO | : International Civil Aviation Organization |
| IMDG-CODE | : International maritime dangerous goods code |
| LD50 | : Lethal Dose, 50% |
| NFPA | : National Fire Protection Association |
| NIOSH | : The National Institute for Occupational Safety and Health |
| OSHA | : Occupational Safety and Health Administration |
| OSHA | : Occupational Safety and Health Administration |
| STEL | : Short Term Exposure Limit |
| TWA | : Time Weighted Average |
| WHMIS | : Workplace Hazardous Materials Information System |

NFPA – USA

Health : 0 Flammability : 1 Reactivity : 0

HMIS

Health : 0 Flammability : 1 Reactivity : 0

SDS Information

GHS Revision : 7

Revision Date : 18/03/2021

Print Date : 18/03/2021 13:27:15

The information above is believed to be accurate and represents the best of our knowledge, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.